

ISE Advantage

Stainless Steel Ice Storage Equipment



Features

- Stainless steel front and sides with galvanized steel back and bottom
- Large opening for scoop dispensing
- · Seamless polyethylene liner with coved corners
- 1 ½" foamed in-place polyurethane insulation
- Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows

705

| 30" Single Door Upright | | | | | | | | |
|-------------------------|--------------|----------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 705-SS | 741 lbs | 30" | 34" | 58" | 240lbs | | | |
| Add 10.5" | to depth for | or snout | | | | | | |



| 30" Single Door Upright | | | | | | | | |
|-------------------------|--------------|---------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 905-SS | 1023lbs | 30" | 34" | 78" | 285lbs | | | |
| Add 10.5 | " to depth f | or snou | t | | | | | |









Features

- Stainless steel front, sides, back, bottom and liner
- Large opening for scoop dispensing
- ½" foamed in-place polyurethane insulation
- Stainless steel baffle prevents ice overflow
- Adjustable feet
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows



| 36" Single Door Upright | | | | | | | | |
|-------------------------|--------------|----------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 965-SBB | 1069lbs | 36" | 34" | 67" | 295lbs | | | |
| Add 10.5' | ' to depth f | or snout | | | | | | |







Features

- Stainless steel front and sides with galvanized steel back and bottom
- · Large opening for scoop dispensing
- Seamless polyethylene liner with coved corners
- 1 ½" foamed in-place polyurethane insulation
- · Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows

1045

| 48" Single Door Upright | | | | | | | | |
|-------------------------|------------|---------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 1045-SS | 1161lbs | 48" | 34" | 55" | 280lbs | | | |
| Add 10.5" | to depth f | or snou | t | | | | | |



| 48" Single Door Upright | | | | | | | | |
|-------------------------|-------------|----------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 1315-SS | 1457lbs | 48" | 34" | 67" | 320lbs | | | |
| Add 10.5" | to depth fo | or snout | | | | | | |











Features

- Stainless steel front and sides with galvanized steel back and bottom
- · Large opening for scoop dispensing
- Seamless polyethylene liner with coved corners
- 1 ½" foamed in-place polyurethane insulation
- Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows

1325

| 60" Single Door Upright | | | | | | | | |
|-------------------------|-------------|---------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 1325-SS | 1471lbs | 60" | 34" | 55" | 310lbs | | | |
| Add 10.5" | to depth fo | r snout | | | | | | |



| 60" Single Door Upright | | | | | | | | |
|-------------------------|------------------------------|-------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 1665-SS | 1846lbs | 60" | 34" | 67" | 370lbs | | | |
| Add 10.5" | Add 10.5" to depth for snout | | | | | | | |







Features

- Full stainless steel—front, back, bottom, sides and liner
- Large opening for scoop dispensing
- 1 ½" foamed in-place polyurethane insulation
- Stainless steel baffle prevents ice overflow
- · Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- · Transparent view windows

1915

| 60" Single Door Upright | | | | | | | | |
|--|---------|-----|-----|-----|--------|--|--|--|
| Model Capacity Width Depth Height Weig | | | | | | | | |
| 1915-SBB | 2180lbs | 60" | 48" | 55" | 400lbs | | | |

Add 10.5" to depth for snout lce makers that weigh over 800lbs may require additional reinforcement.



2415

| 60" Single Door Upright | | | | | | | |
|--|---------|-----|-----|-----|--------|--|--|
| Model Capacity Width Depth Height Weight | | | | | | | |
| 2415-SBB | 2725lbs | 60" | 48" | 67" | 525lbs | | |









Features

- Full stainless steel—front, back, bottom, sides and liner
- Large opening for scoop dispensing
- 1 ½" foamed in-place polyurethane insulation
- · Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- · Transparent view windows



1455

| 60" Single Door Upright | | | | | | | | |
|--|---------|-----|-----|-----|--------|--|--|--|
| Model Capacity Width Depth Height Weight | | | | | | | | |
| 1455-SBB | 1818lbs | 72" | 34" | 55" | 470lbs | | | |

Add 10.5" to depth for snout Ice makers that weigh over 800lbs may require additional reinforcement.



2215

| 60" Single Door Upright | | | | | | | |
|--------------------------------------|---------|-----|-----|-----|--------|--|--|
| Model Capacity Width Depth Height We | | | | | | | |
| 2215-SBB | 2576lbs | 72" | 34" | 75" | 625lbs | | |







Features

- Full stainless steel—front, back, bottom, sides and liner
- Large opening for scoop dispensing
- 1 ½" foamed in-place polyurethane insulation
- · Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows

2115

| 72" Double Door Upright | | | | | | | | |
|-------------------------|----------|-------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 2115-SBB | 2639lbs | 72" | 48" | 55" | 600lbs | | | |

Add 10.5" to depth for snout lice makers that weigh over 800lbs may require additional reinforcement.



3225

| 72" Double Door Upright | | | | | | | |
|--|---------|-----|-----|-----|--------|--|--|
| Model Capacity Width Depth Height Weig | | | | | | | |
| 3225-SBB | 3739lbs | 72" | 48" | 75" | 785lbs | | |









Features

- Full stainless steel—front, back, bottom, sides and liner
- · Large opening for scoop dispensing
- 1 ½" foamed in-place polyurethane insulation
- Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows



4325

| 72" Double Door Upright | | | | | | | |
|-------------------------|-------------------------------------|-----|-----|-----|--------|--|--|
| Model | odel Capacity Width Depth Height We | | | | | | |
| 4325-SBB | 4839lbs | 72" | 48" | 96" | 980lbs | | |







Features

- Full stainless steel—front, back, bottom, sides and liner
- Large opening for scoop dispensing
- 1 ½" foamed in-place polyurethane insulation
- · Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows

2845

| 96" Double Door Upright | | | | | | | |
|--------------------------------------|---------|-----|-----|-----|--------|--|--|
| Model Capacity Width Depth Height We | | | | | | | |
| 2845-SBB | 3557lbs | 96" | 48" | 55" | 730lbs | | |

Add 10.5" to depth for snout Ice makers that weigh over 800lbs may require additional reinforcement.



4345

| 72" Double Door Upright | | | | | | |
|---------------------------------------|---------|-----|-----|-----|---------|--|
| Model Capacity Width Depth Height Wei | | | | | | |
| 4345-SBB | 5039lbs | 96" | 48" | 75" | 1200lbs | |











Features

- Full stainless steel—front, back, bottom, sides and liner
- Large opening for scoop dispensing
- 1 ½" foamed in-place polyurethane insulation
- Stainless steel baffle prevents ice overflow
- Factory installed 1" NPS stainless steel drain
- Spring loaded door hinge
- Transparent view windows

5835

| 96" Double Door Upright | | | | | | | |
|---------------------------------------|---------|-----|-----|-----|---------|--|--|
| Model Capacity Width Depth Height Wei | | | | | | | |
| 5835-SBB | 6522lbs | 96" | 48" | 96" | 1300lbs | | |







Upright: Prison Package

| Single Door Upright : Prison Package | | | | | | | | |
|--------------------------------------|----------|-------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 705* | 741lbs | 30" | 34" | 58" | 240lbs | | | |
| 905* | 1023lbs | 30" | 34" | 77" | 285lbs | | | |
| 965* | 1069lbs | 36" | 34" | 67" | 295lbs | | | |
| 1045* | 1161lbs | 48" | 34" | 55" | 280lbs | | | |
| 1315* | 1457lbs | 48" | 34" | 67" | 320lbs | | | |
| 1325* | 1471lbs | 60" | 34" | 55" | 310lbs | | | |
| 1665* | 1846lbs | 60" | 34" | 67" | 370lbs | | | |
| 1915 | 2180lbs | 60" | 48" | 56" | 400lbs | | | |
| 2415 | 2725lbs | 60" | 48" | 68" | 525lbs | | | |

Features

- · Stainless steel snout with lockable door
- Stainless steel view window cover plate(s) with security screws
- · Stainless steel top closure
- 6" flanged feet with 3 1/2" mounting plates

| Double Door Upright : Prison Package | | | | | | | | |
|--------------------------------------|----------|-------|-------|--------|---------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| 1415 | 1818lbs | 72" | 34" | 56" | 470lbs | | | |
| 2115 | 2639lbs | 72" | 48" | 56" | 600lbs | | | |
| 2215 | 2576lbs | 72" | 34" | 76" | 625lbs | | | |
| 2845 | 3557lbs | 96" | 48" | 56" | 730lbs | | | |
| 3225 | 3739lbs | 72" | 48" | 76" | 785lbs | | | |
| 4325 | 48391lbs | 72" | 48" | 96" | 980lbs | | | |
| 4345 | 5039lbs | 96" | 48" | 76" | 1200lbs | | | |
| 5835 | 6522lbs | 96" | 48" | 96" | 1300lbs | | | |











30" Shuttle Plus Storage

Features

- Guillotine for ice dispensing and shovel door access for ice management
- Seamless polyethylene liner with coved corners
- 1 ½" foamed in-place polyurethane insulation
- Factory installed stainless steel drain pan
- Welded 40" base frame
- One (1) 250lbs capacity Poly-cart with foot operated rear drain
- One (1) 48" UHMWP ice paddle



SPS-1

| One Cart Model | | | | | | | | | |
|----------------|-----------------------------|------------|---------|-----|--------|--|--|--|--|
| Model | Capacity Width Depth Height | | | | Weight | | | | |
| SPS-1 | 500lbs | 30" | 36" | 66" | 320lbs | | | | |
| Add 4.5" t | o depth for | r guilloti | ne hand | lle | | | | | |

SPS-1-G

| One Cart Model | | | | | | | | |
|----------------|---|--|--|--|--|--|--|--|
| Model | odel Capacity Width Depth Height Weig | | | | | | | |
| SPS-1-G | 900lbs 30" 48" 80" 370ll | | | | | | | |
| Add 4.5" | Add 4.5" to depth for guillotine handle | | | | | | | |







60" Shuttle Plus Storage

Features

- Guillotines for ice dispensing and shovel door access for ice management
- SPS-2: Seamless polyethylene liner with coved corners
- SPS-2-G: Full Stainless Steel—front, back, bottom, sides and liner
- 1 ½" foamed in-place polyurethane insulation
- Factory installed stainless steel drain pan
- Welded 40" base frame
- Two (2) 250lbs capacity Poly-carts with foot operated rear drain
- One (1) 48" UHMWP ice paddle

SPS-2

| 60" Shuttle Plus Shuttle - Two Cart Model | | | | | | | | | |
|---|----------|-------|-------|--------|--------|--|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | | |
| SPS-2 | 1500lbs | 60" | 36" | 71" | 530lbs | | | | |
| SPS-2-SL | 2500lbs | 60" | 36" | 91" | 690lbs | | | | |
| SPS-2 Sleeve Only | 1000lbs | 60" | 36" | 20" | 180lbs | | | | |

Add 4.5" to depth for guillotine handle Ice makers that weigh over 800lbs may require additional reinforcement



SPS-2-G

| 60" Shuttle Plus Shuttle - Two Cart Model | | | | | | | | | | |
|---|----------|-------|-------|--------|--------|--|--|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | | | |
| SPS-2-G | 1800lbs | 60" | 48" | 71" | 740lbs | | | | | |
| SPS-2-G-SL | 3000lbs | 60" | 48" | 101" | 960lbs | | | | | |
| SPS-2G Sleeve Only | 1200lbs | 60" | 48" | 30" | 280lbs | | | | | |









90" Shuttle Plus Storage

Features

- Guillotines for ice dispensing and shovel door access for ice management
- · Full Stainless Steel—front, back, bottom, sides and liner
- 1 ½" foamed in-place polyurethane insulation
- · Factory installed stainless steel drain pan
- · Welded 40" base frame
- Three (3) 250lbs capacity Poly-carts with foot operated rear drain
- One (1) 48" UHMWP ice paddle







SPS-3

| 60" Shuttle Plus Shuttle - Three Cart Model | | | | | | | | | |
|---|----------|-------|-------|--------|---------|--|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | | |
| SPS-3 | 2000lbs | 90" | 36" | 71" | 950lbs | | | | |
| SPS-3-SL | 3400lbs | 90" | 36" | 101" | 1190lbs | | | | |
| SPS-3 Sleeve Only | 1400lbs | 90" | 36" | 30" | 400lbs | | | | |

Add 4.5" to depth for guillotine handle Ice makers that weigh over 800lbs may require additional reinforcement.



SPS-3-G

| 60" Shuttle Plus Shuttle - Three Cart Model | | | | | | | | | |
|---|---------|-----|-----|------|---------|--|--|--|--|
| Model Capacity Width Depth Height Weigh | | | | | | | | | |
| SPS-3-G | 2400lbs | 90" | 48" | 71" | 1100lbs | | | | |
| SPS-3-G-SL | 4300lbs | 90" | 48" | 101" | 1570lbs | | | | |
| SPS-3G Sleeve Only | 1900lbs | 90" | 48" | 30" | 500lbs | | | | |







36" & 48" Ice Fill Station

Features

- Large snout opening for scoop dispensing with stainless baffle to prevent ice overflow and guillotine for ice dispensing.
- Full Stainless Steel—front, back, bottom, sides and liner
- 1 ½" foamed in-place polyurethane insulation
- · Factory installed stainless steel drain pan
- Welded 40" base frame
- Transparent view windows
- One (1) 250lbs capacity Poly-cart with foot operated rear drain
- Include 48" UHMWP ice paddle

36" Ice Fill Station

| 36" Ice Fill Station - Single Cart Model | | | | | | | | |
|--|-----------|---------|---------|----------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| IFS900-250 | 1069lbs | 36" | 34" | 112 | 360lbs | | | |
| Add 10.5" to lce makers t additional re | hat weigh | over 80 | 0lbs ma | y requir | е | | | |



48" Ice Fill Station

| 48" Ice Fill Station - Single Cart Model | | | | | | | | | |
|--|-------------|----------|------------------|-----------|--------|--|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | | |
| IFS1000-250 | 1161lbs | 48" | 34" | 89" | 400lbs | | | | |
| IFS1200-250 | 1457lbs | 48" | 34" | 101" | 440lbs | | | | |
| Add 10.5" to lce makers the additional rei | nat weigh o | over 800 | Olbs ma <u>y</u> | y require |) | | | | |









60" Ice Fill Station

Features

- Large snout opening for scoop dispensing with stainless baffle to prevent ice overflow and guillotine for ice dispensing.
- Full Stainless Steel—front, back, bottom, sides and liner
- 1 ½" foamed in-place polyurethane insulation
- Factory installed stainless steel drain pan
- Welded 40" base frame
- Transparent view windows
- One (1) 250lbs capacity Poly-cart with foot operated rear drain
- Include 48" UHMWP ice paddle



60" Ice Fill Station

| 60" Ice Fill Station - Single Cart Model | | | | | | | | | |
|--|----------|-------|-------|--------|--------|--|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | | |
| IFS1300-250 | 1471lbs | 60" | 34" | 89" | 480lbs | | | | |
| IFS1600-250 | 1846lbs | 60" | 34" | 101" | 530lbs | | | | |
| IFS1800-250 | 2180lbs | 60" | 48" | 89" | 575lbs | | | | |
| IFS2300-250 | 2725lbs | 60" | 48" | 101" | 630lbs | | | | |







72" & 96" Ice Fill Station

72" Ice Fill Station

| 72" Ice Fill Station - Double Cart Model | | | | | | | | | |
|--|----------|-------|-------|--------|--------|--|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | | |
| IFS1700-250 | 1818lbs | 72" | 34" | 89" | 685lbs | | | | |
| IFS2400-250 | 2576lbs | 72" | 34" | 109" | 875lbs | | | | |
| IFS2500-250 | 2639lbs | 72" | 48" | 89" | 800lbs | | | | |
| IFS2700-250 | 3739lbs | 72" | 48" | 109" | 940lbs | | | | |

Add 10.5" to depth for snout Ice makers that weigh over 800lbs may require additional reinforcement

Features

- Large snout opening for scoop dispensing with stainless baffle to prevent ice overflow and guillotine for ice dispensing.
- Full Stainless Steel—front, back, bottom, sides and liner
- 1 ½" foamed in-place polyurethane insulation
- · Factory installed stainless steel drain pan
- · Welded 40" base frame
- Transparent view windows
- Two (2) 250lbs capacity Poly-carts with foot operated rear drain
- Include 48" UHMWP ice paddle



96" Ice Fill Station

| 96" Ice Fill Station - Single Cart Model | | | | | | | | |
|--|-----------|-------|-------|--------|---------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| IFS3500-250 | 3557lbs | 96" | 48" | 89" | 845lbs | | | |
| IFS3400-250 | 5039lbs | 96" | 48" | 109" | 1280lbs | | | |
| IFS4800-250 | 6522lbs | 96" | 48" | 130" | 1370lbs | | | |
| Λ -1 -1 40 Γ" +- | l tl. f . | | | | | | | |









Ice Dispenser & Bagger



Features

- <u>Standard Features</u>—Foot pedal activated ice dispensing and timed agitation
- <u>IBU Options</u>— timed dispensing (push button dispensing in place of foot pedal), bag blower and wicket assembly
- · Seamless polyethylene line with coved corners
- 1 ½" foamed in-place polyurethane insulation
- · Fully welded stainless steel augers and agitators
- · Adjustable bag shelf
- · Factory installed drain
- Welded base frame

Not to be used with softer ice such as Flake, Nugget or Chewblet Ice

DISP-500

| Ice Storage Dispenser | | | | | | | | |
|-----------------------|--|-----|-----|-----|--------|--|--|--|
| Model | Model Capacity Width Depth Height Weight | | | | | | | |
| DISP-500 | 647lbs | 30" | 36" | 71" | 510lbs | | | |

Electrical 110V, single phase, 15 amps, 60 hz Add Add 16.5" to depth for chain guard and bag shelf



DISP-1000

| Ice Storage Dispenser | | | | | | | | | |
|--|-------------|---------|-------|---------|--------|--|--|--|--|
| Model Capacity Width Depth Height Weight | | | | | | | | | |
| DISP-1000 1078lbs 48" 36" 72" 590lbs | | | | | | | | | |
| Clootrical 1 | 110\/ aipal | o phood | 15 am | 20 60 h | - ^ dd | | | | |

Electrical 110V, single phase, 15 amps, 60 hz Add Add 16.5" to depth for chain guard and bag shelf







Ice Dispenser & Bagger

Features

- <u>Standard Features</u>—Foot pedal activated ice dispensing and timed agitation
- <u>IBU Options</u>— timed dispensing (push button dispensing in place of foot pedal), bag blower and wicket assembly
- · Full stainless steel-front, back, bottom, sides and liner
- 1 ½" foamed in-place polyurethane insulation
- · Fully welded stainless steel augers and agitators
- Adjustable bag shelf
- Factory installed drain
- · Welded base frame

Not to be used with softer ice such as Flake, Nugget or Chewblet Ice



DISP-2000

| 72" Ice Storage Dispenser | | | | | | | |
|--|---------|-----|-----|-----|---------|--|--|
| Model Capacity Width Depth Height Weight | | | | | | | |
| DISP-2000 | 2254lbs | 72" | 48" | 72" | 1180lbs | | |

Electrical 240V, hard wire, single phase, 30 amps, 60 hz Add 16.5" to depth for chain guard and bag shelf







Ice & Water Dispenser





Features

- <u>Standard</u> Foot pedal activated ice dispensing and two manual water spigot stations
- <u>Touch-Free</u>—Foot pedal activated ice and water dispensing
- Timed agitation
- · Single water inlet connection
- Meets OSHA Requirements and Complies with California T8CCR-3395
- · Seamless polyethylene liner with coved corners
- · Fully welded stainless steel auger and agitator

Not to be used with softer ice such as Flake, Nugget or Chewblet Ice

DISP-IND

| le | | | | | |
|------------------------------------|----------|-------|-------|--------|--------|
| Model | Capacity | Width | Depth | Height | Weight |
| DISP-500-IND | 647lbs | 30" | 36" | 71" | 585lbs |
| DISP-1000-IND | 1078lbs | 48" | 36" | 71" | 755lbs |
| Electrical 110\ Add 23" to dept | | | | | |

DISP-IND-TF

| Touch-Free Ice & Water Dispenser | | | | | | | | |
|---|----------|-------|-------|--------|--------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| DISP-500-IND-TF | 647lbs | 30" | 36" | 72" | 585lbs | | | |
| DISP-1000-IND-TF 1078lbs 48" 36" 72" 755lbs | | | | | | | | |
| Electrical 110V Add 23" to depth | | | | | | | | |









Polyethylene Carts

Features

- Polyethylene shell and fully insulated with polyurethane foam
- Center split hinged lids open to the cart sides
- Foot operated rear drain
- · Handles on both ends of cart

PCC-125

| 22" Ice Carts | | | | | | | | |
|----------------------------------|-------------|----------|----------|-----------|------------|--|--|--|
| Model | Capacity | Width | Depth | Height | Weight | | | |
| PCC-125 125lbs 22" 28" 29" 75lbs | | | | | | | | |
| Easily mane | euvered wit | h 5" swi | vel cast | ers (2 wi | th brakes) | | | |



PCC-250

| 22" Ice Carts | | | | | | |
|---------------|----------|-------|-------|--------|---------|--|
| Model | Capacity | Width | Depth | Height | Weight | |
| PCC-250 | 250lbs | 22" | 34" | 34" | 100 lbs | |

Easily maneuvered 5" front swivel, and 10" rear fixed casters Comes standard with all SPS and IFS systems









Stainless Steel Carts

Features

- · Stainless Steel exterior
- · Fully welded interior liner with coved corners
- · Center split hinged lids open to the cart sides
- · Hand style foot-operated drain

CC-250

| 25" Ice Carts | | | | | | |
|---------------|----------|-------|-------|--------|--------|--|
| Model | Capacity | Width | Depth | Height | Weight | |
| CC-250 | 250lbs | 24" | 30" | 34" | 150lbs | |

Rugged 5" Casters, (2) fixed, (2) swivel with brake Add 4" to depth for handle



CC-300

| 25" Ice Carts | | | | | | |
|---------------|----------|-------|-------|--------|--------|--|
| Model | Capacity | Width | Depth | Height | Weight | |
| CC-300 | 300lbs | 24" | 36" | 34" | 150lbs | |

Rugged 5" Casters, (2) fixed, (2) swivel with brake Add 4" to depth for handle











Accessories

Ice Shovel

Ice Shovel

37" long white plastic

Ice Scoop

Ice Scoop

82 oz Polypropylene large hand scoop



Totes



Ice Totes

For use with PCC-125, PCC-250, CC-250, CC-300 Sturdy polyethylene construction



Ice Paddle



Heavy duty white plastic UHMWP Available in 48" or 60" length)









Ice Bagger Kit

Features

- · Stainless Steel construction
- Up to 20lb bag capacity
- Spring clip to hold bags open
- Twist tie holder
- Adjustable shelf for different size bags

| Stand Alone Bagging Kit | | | | | | |
|-------------------------|----------|-------|-------|--------|--------|--|
| Model | Capacity | Width | Depth | Height | Weight | |
| 4080029 | 20lbs | 15" | 14" | 31" | 35lbs | |









Specialty Applications

Commercial bakery and processing plants

- Fully welded stainless liners with coved corners
- No plastic and limited silicone
- Fully welded stainless steel carts
- High-capacity units
- Dividers for multiple styles of ice





Other Industry Applications for Kloppenberg Bins

- Athletic Departments for K-12, Colleges, and Professional Sports Teams
- Utility Companies, Oil & Gas, Construction, and Agriculture
- Golf Courses
- Marinas, General Stores, and Specialty Sporting Stores
- Government Parks & Rec
- Theme Parks and Water Parks











Ice Storage Equipment

Limited Lifetime Warranty

Kloppenberg Products, LLC ("Kloppenberg") warrants to the original purchaser that it will repair or replace at its own expense and discretion the following lifetime product models. Warranty applies to factory defect in material and/or workmanship exclusive to the polyethylene liner and stainless steel bin cabinet:

705 905 1045 1315 1325 1665

ICE SHUTTLE SYSTEM

SPS-1 SPS-1G SPS-2

ICE STORAGE DISPENSER

DISP-500 DISP-1000

Obligations of Kloppenberg are exclusively limited to the original purchaser / registered owner.

Lifetime warranty products must be registered with Kloppenberg within 30 days of installation.

To qualify for subject warranty, Kloppenberg Lifetime products must be installed and maintained in accordance with the procedures set forth in the product manual provided with each unit .

All decisions regarding defects in material, workmanship, accident, alteration, misuse, improper maintenance or installation shall be made by Kloppenberg and shall be final and binding upon both parties.

All claims must submitted directly to Kloppenberg.

Claims for shipments that are damaged are not covered by warranty and must be handled through the carrier.

Kloppenberg assumes no liability for warranted poly liner or cabinet conditions that do not result in an inoperable and unusable state.

The foregoing warranty shall not apply to cosmetic damage, punctures or any outside or internal damage from resulting from foreign objects.

Kloppenberg does not warrant incidental or consequential damages of any kind resulting in whole or in part from misuse or inadequate maintenance of the product or any part thereof.

Kloppenberg assumes no liability for damage of any kind that is a result of alteration or used parts that are not manufactured or approved in writing by Kloppenberg.

This warranty is applicable only in the United States and Canada.

Kloppenberg strongly advises that a pre-determination for any warranty be made by direct contact with Kloppenberg before any service has been called or completed.







Ice Storage Equipment

Manufacturer's Warranty

Obligations of Kloppenberg Products, LLC ("Kloppenberg") are exclusively limited to the original purchaser / registered owner.

Products must be registered with Kloppenberg within 30 days of installation.

Kloppenberg warrants that it will repair or replace at its own expense any commercial ice bin of its manufacture bearing the name Kloppenberg due to a factory defect in material and/or workmanship occurring within the first twelve (12) months from the date of installation or eighteen (18) months from date of shipment providing, the ice bin has been installed, and maintained in accordance with the procedures set forth in the product manual provided with each ice bin.

This warranty does not include parts or labor coverage for a factory component failure, or other damage resulting from:

- Failure to clean and maintain as set forth in the product manual
- Adverse operating conditions
- Drain line malfunctions
- Water content irregularities for any reason

All decisions regarding defects in material or workmanship or accident, alteration or misuse or improper maintenance or installation shall be made by Kloppenberg and shall be final and binding upon the parties. All claims must include the ice bin model number, serial number, original date of installation and customer identification.

This warranty is applicable only in the United States and Canada.

Kloppenberg assumes no liability for incidental or consequential damages of any kind or for any damages resulting in whole or in part from misuse or inadequate maintenance or the product or any part thereof.

THE WARRANTY DESCRIBED SHALL BE IN LIEU OF ANY OTHER WARRANTY EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

ALL SUBJECT WARRANTY CLAIMS MUST BE PREAUTHORIZED







