

# U-LINE COMMERCIAL



## THE FOUNDATION

EXPLORE REACH-IN, UNDERCOUNTER, AND BASE REFRIGERATION



## THE FOUNDATION

From preserving produce in the kitchen to displaying fresh desserts by the checkout counter, reach-in refrigerators and freezers are the foundation of any foodservice operation. Available in a wide variety of sizes with glass and solid door options, U-Line Commercial offers trusted reach-in freezers and refrigerators that give staff confidence in keeping ingredients and prepared foods fresh. Featuring easy-to-use digital controls, stainless steel interiors and exteriors, and high-performance compressors, our thoughtfully designed refrigeration will improve the flow and function of your space.

Looking for a space saving solution? Make the most of your kitchen with our wide range of undercounter refrigerators and freezers. Convenient cold storage undercounter is ideal for even the smallest spaces. Our refrigerator and freezer chef bases allow you to place additional equipment on top to create the ultimate prep and storage chef station. Sturdy casters provide easy movement for an easy-to-clean environment. These smart refrigeration solutions deliver functionality where you need it most.



**EXPLORE GLASS AND SOLID DOOR  
REACH-IN REFRIGERATORS & FREEZERS**

**EXPLORE UNDERCOUNTER MODELS AND  
BASE REFRIGERATORS & FREEZERS**



U-LINE  
by Desmon

^ ↓  
SET  
v

39

⊖ ⊕





**25 cu ft Refrigerator,  
Reach-In, Solid Door  
UCRE427-SS01A**



**25 cu ft Refrigerator,  
Reach-In, Solid Door  
UCRE527-SS41A**



**25 cu ft Refrigerator,  
Reach-In, Glass Door  
UCRE527-SG41A**



**48 cu ft Refrigerator,  
Reach-In, Solid Door  
UCRE455-SS71A**

## Features and Specifications

- Shelves fit 18" x 26" sheet pans
- Electronic digital temperature control with alarms
- Stainless steel interior and exterior with lock
- Temperature range: 28°F to 46°F
- Self-lubricating, sealed cast iron evaporator fan motor with high volume airflow design
- High efficiency compressor, top mount
- High efficiency evaporator coil & condenser
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high-density polyurethane insulated cabinet
- Environmentally friendly R290 Refrigerant
- NSF/ANSI Standard 7 compliant
- Casters included
- Dimensions
  - + UCRE427-SS01A: 80 23/32" H x 27 9/16" W x 31 1/2" D
  - + UCRE527-SS41A: 82 9/32" H x 26 57/64" W x 31 1/2" D
  - + UCRE527-SG41A: 82 9/32" H x 26 57/64" W x 31 1/2" D
  - + UCRE455-SS71A: 80 23/32" H x 55 1/8" W x 31 1/2" D

- Shelving / Internal Volume
  - + UCRE427-SS01A: 3 epoxy coated wire shelves / 25 cu ft
  - + UCRE527-SS41A: 3 epoxy coated wire shelves / 25 cu ft
  - + UCRE527-SG41A: 3 epoxy coated wire shelves / 25 cu ft
  - + UCRE455-SS71A: 2 sections, 6 epoxy coated wire shelves / 48 cu ft

## Accessories

- Shelf Guide (ULA4080584)
- Epoxy Coated Wire Shelf (20.86" x 25.6") (ULAQ32-0002)
- Light kit for UCRE427-SS01A & UCRE455-SS71A (ULA80110300)



**49 cu ft Refrigerator,  
Reach-In, Solid Door  
UCRE553-SS71A**

**49 cu ft Refrigerator,  
Reach-In, Glass Door  
UCRE553-SG71A**

**74 cu ft Refrigerator,  
Reach-In, Solid Door  
UCRE585-SS71A**

**74 cu ft Refrigerator,  
Reach-In, Glass Door  
UCRE585-SG71A**

## Features and Specifications

- Shelves fit 18" x 26" sheet pans
- Electronic digital temperature control with alarms
- Stainless steel interior and exterior with lock
- Temperature range: 28°F to 46°F
- Self-lubricating, sealed cast iron evaporator fan motor with high volume airflow design
- High efficiency compressor, top mount
- High efficiency evaporator coil & condenser
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high-density polyurethane insulated cabinet
- Environmentally friendly R290 Refrigerant
- NSF/ANSI Standard 7 compliant
- Casters included
- Dimensions
  - + UCRE553-SS71A: 82 9/32" H x 52 9/16" W x 31 1/2" D
  - + UCRE553-SG71A: 82 9/32" H x 52 9/16" W x 31 1/2" D
  - + UCRE585-SS71A: 83 15/32" H x 85 3/64" W x 31 15/32" D
  - + UCRE585-SG71A: 83 15/32" H x 85 3/64" W x 31 15/32" D

- Shelving / Internal Volume
  - + UCRE53-SS71A: 2 sections, 6 epoxy coated wire shelves / 49 cu ft
  - + UCRE53-SG71A: 2 sections, 6 epoxy coated wire shelves / 49 cu ft
  - + UCRE85-SS71A: 3 sections, 9 epoxy coated wire shelves / 74 cu ft
  - + UCRE85-SG71A: 3 sections, 9 epoxy coated wire shelves / 74 cu ft

## Accessories

- Shelf Guide (ULA4080584)
- Epoxy Coated Wire Shelf (20.86" x 25.6") (ULAQ32-0002)



**25 cu ft Freezer,  
Reach-In, Solid Door  
UCFZ427-SS01A**



**25 cu ft Freezer,  
Reach-In, Solid Door  
UCFZ527-SS31A**



**25 cu ft Freezer,  
Reach-In, Glass Door  
UCFZ527-SG31A**



**48 cu ft Freezer,  
Reach-In, Solid Door  
UCFZ455-SS71A**

## Features and Specifications

- Shelves fit 18" x 26" sheet pans
- Electronic digital temperature control with alarms
- Stainless steel interior and exterior with lock
- Temperature range: -13°F to 14°F
- Self-lubricating, sealed cast iron evaporator fan motor with high volume airflow design
- High efficiency compressor, top mount
- High efficiency evaporator coil & condenser
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high-density polyurethane insulated cabinet
- Environmentally friendly R290 Refrigerant
- NSF/ANSI Standard 7 compliant
- Casters included
- Dimensions
  - + UCFZ427-SS01A: 80 23/32" H x 27 9/16" W x 31 1/2" D
  - + UCFZ527-SS31A: 82 9/32" H x 26 57/64" W x 31 1/2" D
  - + UCFZ527-SG31A: 82 9/32" H x 26 57/64" W x 31 1/2" D
  - + UCFZ455-SS71A: 80 23/32" H x 55 1/8" W x 31 1/2" D

- Shelving / Internal Volume
  - + UCFZ427-SS01A: 3 epoxy coated wire shelves / 25 cu ft
  - + UCFZ527-SS31A: 3 epoxy coated wire shelves / 25 cu ft
  - + UCFZ527-SG31A: 3 epoxy coated wire shelves / 25 cu ft
  - + UCFZ455-SS71A: 2 sections, 6 epoxy coated wire shelves / 48 cu ft

## Accessories

- Shelf Guide (ULA4080584)
- Epoxy Coated Wire Shelf (20.86" x 25.6") (ULAQ32-0002)
- Light kit for UCFZ427-SS01A & UCFZ455-SS71A (ULA80110300)



**49 cu ft Freezer,  
Reach-In, Solid Door  
UCFZ553-SS71A**

**49 cu ft Freezer,  
Reach-In, Glass Door  
UCFZ553-SG71A**

**74 cu ft Freezer,  
Reach-In, Solid Door  
UCFZ585-SS71A**

**74 cu ft Freezer,  
Reach-In, Glass Door  
UCFZ585-SG71A**

## Features and Specifications

- Shelves fit 18" x 26" sheet pans
- Electronic digital temperature control with alarms
- Stainless steel interior and exterior with lock
- Temperature range: -13°F to 14°F
- Self-lubricating, sealed cast iron evaporator fan motor with high volume airflow design
- High efficiency compressor, top mount
- High efficiency evaporator coil & condenser
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included
  - + UCFZ553-SS71A, UCFZ553-SG71A: NEMA 5-15P
  - + UCFZ585-SS71A, UCFZ585-SG71A: NEMA 5-20P
- CFC-free high-density polyurethane insulated cabinet
- Environmentally friendly R290 Refrigerant
- NSF/ANSI Standard 7 compliant
- Casters included
- Dimensions
  - + UCFZ553-SS71A: 82 9/32" H x 52 9/16" W x 31 1/2" D
  - + UCFZ553-SG71A: 82 9/32" H x 52 9/16" W x 31 1/2" D
  - + UCFZ585-SS71A: 83 15/32" H x 85 3/64" W x 31 15/32" D
  - + UCFZ585-SG71A: 83 15/32" H x 85 3/64" W x 31 15/32" D

- Shelving / Internal Volume
  - + UCFZ53-SS71A: 2 sections, 6 epoxy coated wire shelves / 49 cu ft
  - + UCFZ53-SG71A: 2 sections, 6 epoxy coated wire shelves / 49 cu ft
  - + UCFZ85-SS71A: 3 sections, 9 epoxy coated wire shelves / 74 cu ft
  - + UCFZ85-SG71A: 3 sections, 9 epoxy coated wire shelves / 74 cu ft

## Accessories

- Shelf Guide (ULA4080584)
- Epoxy Coated Wire Shelf (20.86" x 25.6") (ULAQ32-0002)





# CHEF BASE REFRIGERATORS



**36" Refrigerator  
Chef Base  
UCRB536-SS61A**



**48" Refrigerator  
Chef Base  
UCRB548-SS61A**



**60" Refrigerator  
Chef Base  
UCRB560-SS61A**



**72" Refrigerator  
Chef Base  
UCRB572-SS61A**

## Features and Specifications

- AISI 304 stainless steel interior and exterior
- Electronic digital temperature control with alarms
- Temperature range: 28°F - 46°F
- High efficiency compressor, side mount
  - + UCRB536-SS61A, UCRB548-SS61A, UCRB560-SS61A: 7.3 Running amps
  - + UCRB572-SS61A: 8.7 Running Amps
- High efficiency evaporator coil & condenser
- Self-lubricating, sealed cast iron evaporator fan motor with high volume airflow design
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high-density polyurethane insulated cabinet
- Environmentally friendly R449a refrigerant
- NSF/ANSI Standard 7 compliant
- Dimensions
  - + UCRB536-SS61A: 26" H x 36" W x 32 1/2" D
  - + UCRB548-SS61A: 26" H x 48" W x 32 1/2" D
  - + UCRB560-SS61A: 26" H x 60" W x 32 1/2" D
  - + UCRB572-SS61A: 26" H x 72" W x 32 1/2" D
- Capacity
  - + UCRB536-SS61A: 2 drawers holds (2) standard size GN1/1 (12"x20"x4") pans (not included)
  - + UCRB548-SS61A: 2 drawers holds (4) standard size GN1/1 (12"x20"x4") pans (not included)
  - + UCRB560-SS61A: 2 drawers holds (4) standard size GN1/1 (12"x20"x4") pans (not included)
  - + UCRB572-SS61A: 4 drawers holds (8) standard size GN1/1 12"x20"x4" pans (not included)







# CHEF BASE FREEZERS



**36" Freezer  
Chef Base  
UCFB536-SS61A**



**48" Freezer  
Chef Base  
UCFB548-SS61A**



**60" Freezer  
Chef Base  
UCFB560-SS61A**



**72" Freezer  
Chef Base  
UCFB572-SS61A**

## Features and Specifications

- AISI 304 stainless steel interior and exterior
- Electronic digital temperature control with alarms
- Temperature range: -13°F to 14°F
- High efficiency compressor, side mount
  - + UCFB536-SS61A, UCFB548-SS61A, UCFB560-SS61A: 7.3 Running amps
  - + UCFB572-SS61A: 8.7 Running Amps
- High efficiency evaporator coil & condenser
- Self-lubricating, sealed cast iron evaporator fan motor with high volume airflow design
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high-density polyurethane insulated cabinet
- Environmentally friendly R449a refrigerant
- NSF/ANSI Standard 7 compliant
- Dimensions
  - + UCFB536-SS61A: 26" H x 36" W x 32 1/2" D
  - + UCFB548-SS61A: 26" H x 48" W x 32 1/2" D
  - + UCFB560-SS61A: 26" H x 60" W x 32 1/2" D
  - + UCFB572-SS61A: 26" H x 72" W x 32 1/2" D
- Capacity
  - + UCFB536-SS61A: 2 drawers holds (2) standard size GN1/1 (12"x20"x4") pans (not included)
  - + UCFB548-SS61A: 2 drawers holds (4) standard size GN1/1 (12"x20"x4") pans (not included)
  - + UCFB560-SS61A: 2 drawers holds (4) standard size GN1/1 (12"x20"x4") pans (not included)
  - + UCFB572-SS61A: 4 drawers holds (8) standard size GN1/1 12"x20"x4" pans (not included)





# UNDERCOUNTER REFRIGERATORS



**2 Door Refrigerator,  
Undercounter  
UCRE552-SS61A**



**3 Door Refrigerator,  
Undercounter  
UCRE570-SS61A**



**4 Door Refrigerator,  
Undercounter  
UCRE588-SS61A**

## Features and Specifications

- AISI 304 stainless steel interior and exterior
- Electronic Control
- Autodefrost
- Temperature range: 28°F to 46°F
- Epoxy coated, sealed evaporator eliminates potential corrosion
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high density polyurethane insulated cabinet
- Environmentally friendly R449a refrigerant
- NSF/ANSI Standard 7 compliant
- Dimensions
  - + UCRE552-SS61A: 33" H x 57 <sup>15</sup>/<sub>32</sub>" W x 27 <sup>9</sup>/<sub>16</sub>" D
  - + UCRE570-SS61A: 33" H x 76 <sup>37</sup>/<sub>64</sub>" W x 27 <sup>9</sup>/<sub>16</sub>" D
  - + UCRE588-SS61A: 33" H x 95 <sup>43</sup>/<sub>64</sub>" W x 27 <sup>9</sup>/<sub>16</sub>" D
- Internal Volume
  - + UCRE552-SS61A: 9.88 cu ft, 2 epoxy coated shelves
  - + UCRE570-SS61A: 15.57 cu ft, 3 epoxy coated shelves
  - + UCRE588-SS61A: 21.2 cu ft, 4 epoxy coated shelves





# UNDERCOUNTER FREEZERS



**2 Door Freezer,  
Undercounter  
UCFZ552-SS61A**



**3 Door Freezer,  
Undercounter  
UCFZ570-SS61A**



**4 Door Freezer,  
Undercounter  
UCFZ588-SS61A**

## Features and Specifications

- AISI 304 stainless steel interior and exterior
- Electronic Control
- Autodefrost
- Temperature range: -13°F to 14°F
- Epoxy coated, sealed evaporator eliminates potential corrosion
- Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P
- CFC-free high density polyurethane insulated cabinet
- Environmentally friendly R449a refrigerant
- NSF/ANSI Standard 7 compliant
- Dimensions
  - + UCFZ552-SS61A: 33" H x 57 15/32" W x 27 9/16" D
  - + UCFZ570-SS61A: 33" H x 76 37/64" W x 27 9/16" D
  - + UCFZ588-SS61A: 33" H x 95 43/64" W x 27 9/16" D
- Internal Volume
  - + UCFZ552-SS61A: 9.88 cu ft, 2 epoxy coated shelves
  - + UCFZ570-SS61A: 15.57 cu ft, 3 epoxy coated shelves
  - + UCFZ588-SS61A: 21.2 cu ft, 4 epoxy coated shelves





# THE FOUNDATION

- Reach-in refrigeration and freezer solutions in a wide variety of sizes and configurations
- Easy to use digital control systems
- Robust stainless steel interiors and exteriors
- High-performance compressors ensure safe food storage
- CFC-free high-density polyurethane insulated cabinets
- NSF/ANSI Standard 7 compliant
- 1 Year (parts and labor) / 5 year sealed system (parts) – See complete warranty for details

**SEE ALL THAT U-LINE COMMERCIAL HAS TO OFFER**



Reach-In Refrigerators & Freezers • Dispensers • Ice Machines • Undercounter Refrigeration & Wine • Back Bar Refrigeration • Blast Chillers & Shock Freezers  
Base Refrigerators & Freezers • Pizza & Food Prep Tables

THE MIDDLEY CORPORATION

